

Type of Installation: Pole  
 Type of Protection: **IP 65**  
 Protection Class: I  
 Lamp/Wattage: 3 x HIT-TC-CE 20 W  
 Dimensions: B 220, H 190, AL 550  
 Colour: anthracite metallic

Housing: aluminium extrusion profile, powder-coated. Pole top: die-cast aluminium, powder-coated. Housing covers: die-cast aluminium, powder-coated. Transparent safety glass. Module inserts with asymmetric reflectors: aluminium, highly polished anodised finish. Luminaire tilted horizontally 15° upwards. 1 to 3 modular extension brackets, according to pole top design. As standard with Gore-TM Protective Vents membrane valve. Mains supply via 6m connecting cable. Pole tops are designed for accomodation of flanges of various sizes. Flanges must be ordered separately.

**Electro-technics:**

Voltage 220 - 240 V / 50 - 60 Hz  
 Electric Gear EB

**Testings:**

Country Code CE  
 Glow Wire Test 960°C - 30 seconds  
 Impact Protection (IK-Value) IK10 (20 Joule)  
 Protection Class I  
 Other Marks WEEE mark  
 Energy Effizienz Class A+  
 conventional lamp  
 Safety Marks F-mark  
 Type of Protection **IP 65**

**Modules**

90-6054.0031	D 148, H 60 mm	for 60 mm pole diameter anthracite metallic
90-6054.004	D 148, H 60 mm	for 60 mm pole diameter silver metallic
90-6055.0031	D 148, H 60 mm	for 76 mm pole diameter anthracite metallic
90-6055.004	D 148, H 60 mm	for 76 mm pole diameter silver metallic
90-6056.0031	D 148, H 60 mm	for 90 mm pole diameter anthracite metallic
90-6056.004	D 148, H 60 mm	for 90 mm pole diameter silver metallic

**Lamp 1:**

Number of Lamps 1 3  
 Light colour  
 Lebensdauer  
 Lamp 1 HIT-TC-CE  
 Socket PGJ5  
 Wattage 20,00 W

**Lamp 2:**


Lebensdauer Lampe

**Weights and measures:**

Projection 550 mm  
 Height H 190 mm  
 Weight 19,1 kg  
 Width B 220 mm

**Lighting technology:**

Light Output Ratio 47,3 %  
 Luminaire Beam Angle -



**Modules**

**Pole-fitters for Slopia Sky series**