

551087.002.12



Series: Mondana®-E PE Recessed ceiling and wall luminaires

Type of Installation: Recessed ceiling mounting, Wall (recessed)
 Type of Protection: **IP 65**
 Protection Class: I
 Lamp/Wattage: 1 x LED 8,7 4000 K / 620 lm
 Dimensions: D 352, H 2
 Colour: white

Mounting support body plastic (polycarbonate), micro-textured coating, cover fixed by screw-on thread, cover plastic (polyethylene) opal, satin finish, fitted as standard with Gore-TM Protective Vents diaphragm valve, with recessed housing metal, powder-coated, for installation in hollow walls with wall thicknesses of 10-30mm.



Electro-technics:

System Power 9 W
 Electric Gear ohne Betriebsgerät
 Voltage 220 - 240 V / 50 Hz

Testings:

Safety Marks F-mark
 Type of Protection **IP 65**
 Impact Protection (IK-Value) IK10 (20 Joule)
 Other Marks WEEE mark
 Energy Efficiency Class of included lamp A+
 Glow Wire Test 650°C - 30 seconds
 Protection Class I
 Energy Efficiency Class LED A+
 Country Code CE

Lamp 1:

Lamp 1 LED
 Wattage 8,70 W
 Light colour 840
 Number of Lamps 1
 Colour Temperature 4000K
 Lebensdauer

Lamp 2:


Lebensdauer Lampe

Weights and measures:

Height H 2 mm
 Ceiling Thickness 10-30 mm
 Ceiling cut-out DA 325 mm
 Weight 2,01 kg
 Diameter D 352 mm
 Recess Depth 120 mm

Lighting technology:

Luminaire flux 650 lm
 Colour Rendering Index (CRI) 80



Accessories

Concrete box

981632.002 D 330, H 125 for Mondana-E 350 blank

Replacement parts

Replacement diffusers

08-2036.002 Ersatzdiffusor PE D 280

RZB

551087.002.12



This luminaire comes complete with integrated LED light source.



L
E
D

This luminaire is fitted with a fixed light source which cannot be replaced.

874/2012

