

# 551086.002.12



Series: Mondana®-E Opal glass Recessed ceiling and wall luminaires

Type of Installation: Recessed ceiling mounting, Wall (recessed)  
Type of Protection: **IP 65**  
Protection Class: I  
Lamp/Wattage: 1 x LED 8,7 4000 K / 510 lm  
Dimensions: D 352, H 2  
Colour: white

Mounting support body plastic, micro-textured coating, cover fixed by screw-on thread, cover opal glass, satin finish, hand-blown, fitted as standard with Gore-TM Protective Vents diaphragm valve, with recessed housing metal, powder-coated, for installation in hollow walls with wall thicknesses of 10-30mm.



### Electro-technics:

System Power 9 W  
Electric Gear ohne Betriebsgerät  
Voltage 220 - 240 V / 50 Hz

### Testings:

Safety Marks F-mark  
Type of Protection **IP 65**  
Impact Protection (IK-Value) IK03 (0,35 Joule)  
Other Marks WEEE mark  
Energy Efficiency Class of included lamp A+  
Glow Wire Test 850°C - 30 seconds  
Protection Class I  
Energy Efficiency Class LED A+  
Country Code CE

### Lamp 1:

Lamp 1 LED  
Wattage 8,70 W  
Light colour 840  
Number of Lamps 1  
Colour Temperature 4000K  
Lebensdauer

### Lamp 2:


Lebensdauer Lampe

### Weights and measures:

Height H 2 mm  
Ceiling Thickness 10-30 mm  
Ceiling cut-out DA 325 mm  
Weight 2,64 kg  
Diameter D 352 mm  
Recess Depth 120 mm

### Lighting technology:

Luminaire flux 520 lm  
Colour Rendering Index (CRI) 80



### Accessories

#### Concrete box

981632.002 D 330, H 125 for Mondana-E 350 blank

#### Replacement parts

#### Replacement glasses

05-2008.002 Replacement glass D 280, H 88

**RZB**

**551086.002.12**



This luminaire comes complete with integrated LED light source.



L  
E  
D

This luminaire is fitted with a fixed light source which cannot be replaced.

874/2012

