



551100.002.12



Series: Mondana®-E PE Recessed ceiling and wall luminaires

Type of Installation: Recessed ceiling mounting, Wall (recessed)
Type of Protection: **IP 65**
Protection Class: I
Lamp/Wattage: 1 x LED 20,4 4000 K / 1856 lm
Dimensions: D 650, H 2
Colour: white

Mounting support body plastic (polycarbonate), micro-textured coating, cover fixed by screw-on thread, cover plastic (polyethylene) opal, satin finish, fitted as standard with Gore-TM Protective Vents diaphragm valve, with recessed housing metal, powder-coated, for installation in hollow walls with wall thicknesses of 10-30mm.



Electro-technics:

System Power 21 W
Electric Gear ohne Betriebsgerät
Voltage 220 - 240 V / 50 - 60 Hz

Testings:

Safety Marks F-mark
Type of Protection **IP 65**
Impact Protection (IK-Value) IK10 (20 Joule)
Other Marks WEEE mark
Energy Efficiency Class of included lamp A+
Glow Wire Test 650°C - 30 seconds
Protection Class I
Energy Efficiency Class LED A+
Country Code CE

Lamp 1:

Lamp 1 LED
Wattage 20,40 W
Light colour 840
Number of Lamps 1
Colour Temperature 4000K
Lebensdauer

Lamp 2:

Lebensdauer Lampe

Weights and measures:

Height H 2 mm
Ceiling Thickness 10-30 mm
Ceiling cut-out DA 625 mm
Weight 6,13 kg
Diameter D 650 mm
Recess Depth 140 mm

Lighting technology:

Luminaire flux 1.900 lm
Colour Rendering Index (CRI) 80

Accessories

Concrete box

981634.002 D 630, H 150 for Mondana-E 650 blank

Replacement parts

Replacement diffusers

08-2038.002 Ersatzdiffusor PE D 550